

# TECHNICAL DATA SHEET

Product No. 3081



ACN 000 725 833

## CRC Industries (Aust) Pty. Limited

PO Box 199, Castle Hill, NSW 1765.

### I. Product Description

**CRC Belt Grip** provides a temporary, synthetic treatment for worn belts that extends belt life by reducing slippage, hardening, glazing, dirt build-up and friction. **CRC Belt Grip** also helps eliminate annoying squeaks and squeals. Formulated with a tacky, non-drying, water-resistant polymer. **CRC Belt Grip** can be used on leather, rubber, canvas or fabric and is ideally suited for flat, round and V-belts.

### II. Applications

**CRC Belt Grip** is recommended for industrial machinery, conveyor systems, portable motorised equipment and vehicle belts.

### III. Features & Benefits

- Tacky, non-drying film. Minimises drive belt slippage, resists water wash off, maintains belt flexibility and prevents loads from slipping on conveyor systems.
- Improves traction. Reduces belt tension relieving stress on motors, shafts and wheels for improved operating efficiency.
- Colourless. Will not stain finished goods transported on conveyor systems.
- No known ozone depleting chemicals. Offers effective performance while complying with the EPA regulations on the use of ozone depleting chemicals.

### IV. Physical Properties without propellant

<b>Flash Point</b>	<18°C	<b>Boiling Point</b>	70°C
<b>Odour</b>	Solvent	<b>Temperature Range</b>	Continuous - 170°C Intermittent - 200°C
<b>Appearance</b>	Clear Liquid	<b>Specific Gravity</b>	0.7238
<b>Vapour Density</b>	>air	<b>Sara Title III, Sect.313 Chemicals</b>	No
<b>Prop 65</b>	No	<b>Propellant</b>	Hydrocarbon

### V. Specification and Approvals

- M.A.F. Meat Approved C12
- AQIS Category 12 Lubricant Type C

## VI. Performance Characteristics

Type of Film	Tacky, colourless, non-drying
--------------	-------------------------------

## VII. Directions

- Turn off equipment and stop belts before applying.
- Spray a light, even coating on each side of belts in contact with pulleys.
- Re-apply **CRC Belt Grip** periodically to help extend belt and pulley bearing life.
- Do not apply while equipment is energised.

## VIII. Package Description

Part Number: 3081                      Aerosol Size: 400gm

## IX. Disposal

Disposal requirements vary by state and local regulations. All used and unused product should be disposed of in conformance with local, state and commonwealth laws and regulations.

## X. Special Use Warnings

### Aerosol Cans

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

### General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapour and spray mist. Avoid contact with the skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

**PRODUCT WARRANTY:** CRC offers a conditional warranty on this product for the period of 2 years from the date of manufacture.

**DISCLAIMER:** All information on this data sheet is based on testing by CRC Industries (Aust.) Pty. Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust.) Pty. Ltd. makes no representations or warranties of any kind concerning this data.